

Baliecode Slang	Dynamische Werkdruk (BAR)	Huls Type	Slang Afmeting Inwendig		Huls Diameter D	Huls Diameter L	Schil Lengte Binnen mm	Schil Lengte Buiten mm	Pers Diameter mm
			inch	mm					
HSL4SH 34	420	CF 12 I	<b>3/4.</b>	19	38,0	60,0	15,0	52,0	<b>34,0</b>
HSL4SH 1	380	CF 16 I	<b>1.</b>	25	46,0	74,0	17,0	65,0	<b>42,1</b>
HSL4SH 1 1/4	350	CF 20 I	<b>1 1/4.</b>	32	55,0	88,0	21,5	74,0	<b>50,6</b>
HSL4SH 1 1/2	290	CF 24 I	<b>1 1/2.</b>	38	62,0	94,0	22,0	81,0	<b>57,1</b>

**SPECIALE UITVOERING 1" 420 BAR ZET 10 MM UIT TIJDENS HET PERSEN**

<b>HSLR15 1</b>	<b>420</b>	<b>CF 16 I</b>	<b>1.</b>	<b>25</b>	<b>46,0</b>	<b>74,0</b>	<b>17,0</b>	<b>65,0</b>	<b>42,1</b>
-----------------	------------	----------------	-----------	-----------	-------------	-------------	-------------	-------------	-------------

